

# Bird BLazer

World's first indoor laser bird repeller - Remote controlled Fat Beam technology safely frightens birds away

Laser beams are well-documented to chase away pest birds. The beam seeks out their roosting-spots, alarming and confusing them, causing them to flee. This technological breakthrough makes current hand-held, labor-intensive lasers obsolete, opening this proven method of bird control for general industrial use.

- 10 milliwatts of tri-colored fat-beam laser power (yellow, green, red)
- State-of-the-art, fully registered, consumer-safe device
- Works day and night: laser beams constantly change pattern and location to prevent acclimation
- **Model #: BLAZER**



**Coverage:** up to 10,000 feet  
**Pests:** birds (pigeons, sparrows, starlings, swallows), bats, rodents and more  
**Uses:** hangars, warehouses, plants, tunnels, loading docks, train sheds, boat houses, underpasses, storage sheds, sports arenas, convention centers, parking garages, car washes and other enclosed or semi-enclosed area

**SPECIFICATIONS:**  
**Laser Power:** 10mW FAT BEAM  
**Unit Power:** 50 watts  
**Laser Colors:** Green, yellow, red  
**Net Weight:** 9 lbs/4Kgs  
**Power:** AC 100V~120V or 220V~240V, @ 50/60Hz  
**Electric Current:** 110v = 0.45 amps 220v = 0.23 amps  
**Classification:** 3R  
**Size:** 9" x 11" x 6.75"  
**Fuse:** 20mmx2A slow-blow  
**Housing:** Metal  
**Beam Divergence:** < 1.5 mrad  
**Operating Temperature:** 64-77°F/18-25°C  
**Safe Temperature for Use:** 41-104°F/5-40°C



## NEW! Bird-X Laser - Indoor / Bird-X Laser - Outdoor

Laser Technology in convenient, economically-sized units for smaller areas. Now available for outdoor use also (stake or bracket mount) to deter roosting birds, geese on ponds, etc.

- REMOTE CONTROLLED for safety and convenience; includes optional timer function
- State-of-the-art, fully registered, consumer-safe devices
- RED and GREEN Laser beams constantly change to prevent acclimation



**BIRD-X LASER INDOOR - SPECIFICATIONS:**  
**Laser Power:** Red: 650nm100mW, green :532nm50mW  
**Unit Power:** 4.9mW RED+4.9mW GREEN  
**Laser Color:** Red + green  
**Net Weight:** 1.5kg  
**Power:** AC100-240V,50-60Hz  
**Electric Current:** 100mA  
**Classification:** CLASS 3R  
**Size (mm):** L(18.5)\*W(14.8)\*H(7.0) CM  
**Fuse:** 2A  
**Housing:** Cast aluminum  
**Beam Divergence:** 60°  
**Operating Temperature:** 0°C-40°C  
**Safe Temperature for Use:** 0°C-35°C

**BIRD-X LASER OUTDOOR - SPECIFICATIONS:**  
**Laser Power:** Red: 650nm100mW, green :532nm50mW  
**Unit Power:** 1mW RED+1mW GREEN  
**Laser Color:** Red + green  
**Net Weight:** 1.5kg  
**Power:** AC100-240V,50-60Hz  
**Electric Current:** 100mA  
**Classification:** CLASS 3R  
**Size (mm):** L(16.5)\*W(13.8)\*H(13.8) CM  
**Fuse:** 2A  
**Housing:** Cast aluminum  
**Beam Divergence:** 60°  
**Operating Temperature:** -20°C-40°C  
**Safe Temperature for Use:** -10°C-35°C



- Model #'s:**
- BX-LASER-IN
  - BX-LASER-OUT